



## S2000 Series Continuous Inkjet Printer

S2000 series continuous small character inkjet printer is designed for high quality printing and improving production line effectively.

Its print head adopts modular design, and the stainless steel chassis, which can maintain reliable operation in harsh production environment as well as improve the production line effectively.

### Print Head




The nozzle valve adopts direct sealing nozzle hole structure, effectively prevent the ink leakage.

### Ink System



Single print head and recovery diaphragm pump design makes more stable and durable.

### Main Hardware



The main board with newest structure has superior performance of function and stability, and the EHT is dustproof and waterproof, better to deal with the harsh and complex environment.


### External Interface



With grade of IP68, the interface not only supports RS232, network port, but also the counter reset, information control and other functions.

# 🔥 S2000 Series

## Print Head



240 mm

## Front view



550 mm

400 mm

## Side view



250 mm

## Screen



# 🔥 Technical Parameters

## Printing Parameters

Print Head Duct	3m/6m
Nozzle Specifications	40u、50u、60u、75u
Printing Height	2~20mm
Printing Distance	3~30mm
Printing Lines	1~5 lines
Printing Speed	576m/min
Counter	More than 20 independent counters
Ink Color	Black, Red, Blue, Green, White, Invisible
Ink Type	High adhesion, Migration resistance, High temperature resistance, Special for glass, Permeability, Food grade, Oil resistance
Font	5×6L 7×6L 7×10L 9×8L 9×11L 11×11L 16×16L 24×24L 32×32L 11×11B 16×16B 24×24B 32×32B
Printing Material	Carton, Plastic, Metal, Boarding, Pipe, Stone, Cable, Glass, Electronic components, Auto parts, Industrial chemical packaging, Medical / Food / Gift box
Print Content	Text, Time, Date (Julian Year), Logo, Shift, SN, Dynamic Barcode/QR Code, Dynamic Serial Data, Dynamic Database (Additional content can be added as required)

## Machine Parameters

Operating System	Embedded Linux security operating system
Display Screen	10.1-inch color display, industrial touch screen
Communication Interface	Network port, USB, RS232
Protection Level	IP55
Power Parameters	Input 100-240V AC
Rated power	150W
Memory	256M
Machine Material	304 stainless steel
Machine Specifications	400mm×250mm×550mm (Length×width×height)
Working Environment	Temperature 0-45°C / Humidity 30-70%Rh
Related Certification	RoHS、CE、BIS
Net Weight	22kg
Main Hardware	American TI AM3358 industrial grade CPU, American Xilinx Spartan-6 industrial grade FPGA
External Interface	Optical sensor, Encoder, Reverse and upside down control, Signal light alarm output, Serial number output control, External printing information selection
Support Language	Support more than 40 national languages (Chinese, English, Arabic, Danish, German, Russian, French, Finnish, Korean, Japanese, Spanish, Italian, etc.)

# 🔥 Applications



PET plastics

Packing carton

Medicine

Food packaging

Furniture and wood

# 🔥 Printing Samples

5X6	ABCDEFG 12345 5X6
7X6	ABCDEFG 12345 6x7
7X10	ABCDEFG 12345 10x7
9X8	ABCDEFG 12345 8X9
9X11	ABCDEFG 12345 11X9
11X11L	ABCDEFG 12345 11X11
11X11B	ABCDEFG 12345 11X11B
16X16L	ABCDEFG 12345 16X16L
16X16B	ABCDEFG 12345 16X16B
24X24L	ABCDE12345 24X24L
24X24B	ABCDE12345 24X24B
32X32L	ABCDE 12345 32X32L
32X32B	ABCDE 12345 32X32B
5X6(5lines)	ABCDEFGHIJKLmnop ABCDEFGHIJKLmnop ABCDEFGHIJKLmnop ABCDEFGHIJKLmnop ABCDEFGHIJKLmnop
7X6(2lines)	QWERTYUIOP 20210414 1234567890 20210414
7X6(3lines)	QWERTYUIOP 20210414 1234567890 20210414 ABCDEFGHIJKLmnop 123456789
7X6(4lines)	ABCDEFGHIJKLmnop 1234567890 QWERTYUIO PQRSTUVWXYZ 0123456789 09876543210 PQRSTU
LOGO	🏠 📞 📧 📧 📧 📧 📧 📧
Tower	◀ ◁ ▷ ▶ ↻ ↺ ↻ ↺
DM Codes	QR Code
Barcodes	81234567890 6123447890155

# Codpad

Guangzhou Codpad e-tech Company Limited

<https://www.docod-group.com/> sales@docod.com.cn

market@docod.com.cn service@docod.com.cn WhatsApp:+86 139 2896 7650

Add: Room 4, Building 2, NO.27, Hejing Road, LiWan District, Guangzhou, China